

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

		MOI	DEL DA	TA - F(OR COMP	RESSED	AIR			
1	Manufacturer:	FS Cu	rtis							
	Model Number: NxV110-125						Date:	Novembe	r, 2017	
2	X Air-cooled Water-cooled						Type:		Screw	
						i	# of Stages:		1	
3*	Full Load Oper	125		b psig						
4		Drive Motor Nominal Rating)	hp			
5	Drive Motor Nominal Efficiency				96.	2	percent			
6	Fan Motor Nominal Rating (if applicable)				4		hp			
7	Fan Motor Nor	minal Efficie	ency		86.	5		percent		
	Input Power (kW)				Capacity (a	acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d			
	137			624.	1	21.95				
8*	116			542.	6	21.38				
-	95			456.	4	20.82				
-	75			366.	5	20.46				
		41 200					20.50			
9*	Total Package	_	at Zero F	low c, d	0.0			kW		
10	Isentropic Effi	Isentropic Efficiency			71.7	0			%	
11	Specific Power (kW/100 ACFM)	35.00 30.00 25.00 20.00 10.00 0.0 50	Note: Grap	oh is only a vis	250.0 300.0 350.0 Capacity (ACFM) sual representation + SkW/100acfm incr	of the data in S	ection 8	600.0 650.0	700.0	

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
 NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

	olume Flow Rate pecified conditions	Volume Flow Rate	Specific Energy Consumption	Zero Flow Power	
$\underline{m}^3 / \underline{min}$	ft ³ / min	%	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8		
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%	
1.5 to 15	53 to 529.7	+/- 5	+/- 6		
Above 15	Above 529.7	+/- 4	+/- 5		

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.