			Rotary Compressor: Fixed Sp			7
	MODEL DATA - FOR COMPRESSED AIR					
	1	Manufacturer:	facturer: FS Curtis			
		Model Number:	R\$15-175	Date: Type:	4/12/2019 Screw	
	2	X Air-cooled	Water-cooled			
				# of Stages:	1	
	3*	Rated Capacity at Full L	oad Operating Pressure <sup>a, e</sup>	45	acfm <sup>a,e</sup>	
	4*	Full Load Operating Pres	h	175	psig <sup>b</sup>	
	5	Maximum Full Flow Operating Pressure <sup>c</sup>		176	psig <sup>c</sup>	1
	6	Drive Motor Nominal Rating		15	hp	1
	7	Drive Motor Nominal Ef	rive Motor Nominal Efficiency		percent	1
	8	Fan Motor Nominal Rati	ng (if applicable)	93 0.5	hp	-
	9	Fan Motor Nominal Effi	ciency	78.2		-
		, e		3.4	kW <sup>e</sup>	-
	10*	Fotal Package Input Power at Rated Capacity and Full Load				-
	11	Operating Pressure <sup>d</sup>	ating Pressure <sup>d</sup>		$kW^d$	_
	12*	e .	at Rated Capacity and Full Load Operating	29.6	kW/100 cfm <sup>e</sup> Percent	
1		Pressure <sup>e</sup>				-
	13	Isentropic Efficiency		60.58		
<b>:A</b>		<ul> <li>CAGI website for a list of parties</li> <li>a. Measured at the disc ISO 1217, Annex C;</li> <li>b. The operating pressure for this data sheet.</li> <li>c. Maximum pressure a maximum pressure a</li> <li>d. Total package input</li> </ul>	Performance Verification Program, these items are cipants in the third party verification program: harge terminal point of the compressor package in accord ACFM is actual cubic feet per minute at inlet conditions are at which the Capacity (Item 3) and Electrical Consum- nttainable at full flow, usually the unload pressure setting ttainable before capacity control begins. May require ad power at other than reported operating points will vary w in ISO 1217, Annex C, as shown in table below:	<u>www.cagi.org</u> dance with ption (Item 11) were measured for load/no load control or the ditional power.	ministrator.	_
npressed Air & Gas Institute		NOTE: The terms "power" and "energy" are synonymous for purposes of this		s document.	Succific Former	Zana El-
		Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero Flo Power
Member		$\frac{\text{m}^3 / \min}{\text{Below } 0.5}$	<u>ft<sup>3</sup> / min</u> Below 17.6	%	% +/- 8	%
		0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10
		1.5 to 15	53 to 529.7	+/- 5	+/- 6	±/- 10